

REVISIONS			
LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Changes to slew rate test. Changes IAW NOR 5962-R194-93.	93-08-26	M. A. Frye
B	Change boilerplate to add one-part part numbers. Add device type 03. Add delta test limits. Redrawn.	97-06-03	R. Monnin
C	Change to group A subgroups for TCVOOS in table I. Update boilerplate. -rrp	00-10-26	R. Monnin
D	Add device type 01 limits to table IIB. - ro	02-11-22	R. Monnin

THE ORIGINAL FIRST PAGE OF THIS DRAWING HAS BEEN REPLACED.


REV																														
SHEET																														
REV																														
SHEET																														
REV STATUS				REV		D	D	D	D	D	D	D	D	D	D	D	D													
OF SHEETS				SHEET		1	2	3	4	5	6	7	8	9	10	11	12													
PMIC N/A				PREPARED BY Rajesh Pithadia					DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216 http://www.dscc.dla.mil																					
STANDARD MICROCIRCUIT DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A				CHECKED BY Rajesh Pithadia																										
				APPROVED BY Raymond Monnin																										
				DRAWING APPROVAL DATE 88-09-13																										
				REVISION LEVEL D					SIZE A	CAGE CODE 67268		5962-88630																		
SHEET										1 OF 12																				

1. SCOPE


1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device classes Q and M) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels are reflected in the PIN.

1.2 PIN. The PIN is as shown in the following examples.

For device classes M and Q:



For device class V:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. Device class M RHA marked devices meet the MIL-PRF-38535, appendix A specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	AMP-01A	Low-noise, precision, instrumentation amplifier
02	AMP-01B	Low-noise, precision, instrumentation amplifier
03	AMP01	Low-noise, precision, instrumentation amplifier

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as listed below. Since the device class designator has been added after the original issuance of this drawing, device classes M and Q designators will not be included in the PIN and will not be marked on the device.

<u>Device class</u>	<u>Device requirements documentation</u>
M	Vendor self-certification to the requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A
Q or V	Certification and qualification to MIL-PRF-38535

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88630
		REVISION LEVEL D	SHEET 2

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
V	GDIP1-T18 or CDIP2-T18	18	Dual-in-line
3	CQCC1-N28	28	Square leadless chip carrier
K	GDFP2-F24 or CDFP3-F24	24	Flat pack

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

1.3 Absolute maximum ratings. 1/

Supply voltage (V_S)	± 18 V dc
Power dissipation (P_D)	500 mW 2/
Common mode input voltage	Supply voltage
Differential input voltage:	
$R_G \geq 2 \text{ k}\Omega$	± 20 V dc
$R_G < 2 \text{ k}\Omega$	± 10 V dc
Output short circuit duration	Indefinite
Storage temperature range	-65°C to $+150^\circ\text{C}$
Lead temperature (soldering, 60 seconds)	$+300^\circ\text{C}$
Thermal resistance, junction-to-case (θ_{JC})	See MIL-STD-1835
Thermal resistance, junction-to-ambient (θ_{JA}):	
Case V	120°C/W
Case 3	104°C/W
Case K	69°C/W

1.4 Recommended operating conditions.

Supply voltage (V_S)	± 15 V dc
Ambient operating temperature range (T_A)	-55°C to $+125^\circ\text{C}$

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

- 1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
- 2/ Must withstand the added P_D due to short circuit test, e.g., I_{OS} .

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88630
		REVISION LEVEL D	SHEET 3

STANDARDS

DEPARTMENT OF DEFENSE

- MIL-STD-883 - Test Method Standard Microcircuits.
- MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

HANDBOOKS

DEPARTMENT OF DEFENSE

- MIL-HDBK-103 - List of Standard Microcircuit Drawings.
- MIL-HDBK-780 - Standard Microcircuit Drawings.

(Unless otherwise indicated, copies of the specification, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. The individual item requirements for device class M shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V or MIL-PRF-38535, appendix A and herein for device class M.

3.2.1 Case outlines. The case outlines shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table IIA. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-HDBK-103. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535. Marking for device class M shall be in accordance with MIL-PRF-38535, appendix A.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535. The compliance mark for device class M shall be a "C" as required in MIL-PRF-38535, appendix A.

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6.2 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein or for device class M, the requirements of MIL-PRF-38535, appendix A and herein.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88630
		REVISION LEVEL D	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 1/ -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Input bias current	I _B		1	01,03		±4	nA
			2, 3			±10	
			1	02		±6	
			2, 3			±15	
Input offset current	I _{IO}		1	01, 03		1	nA
			2, 3			3	
			1	02		2	
			2, 3			6	
Offset referred to input vs. positive supply	+PSR	V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 1000	1, 2, 3	01, 03	120		dB
		V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 100			110		
		V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 10			95		
		V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 1			75		
		V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 1000		02	110		
		V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 100			100		
		V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 10			90		
		V ₊ = +5 V to +15 V, V ₋ = -15 V, G = 1			70		
Offset referred to input vs. negative supply	-PSR	V ₋ = -5 V to -15 V, V ₊ = +15 V, G = 1000	1, 2, 3	All	105		dB
		V ₋ = -5 V to -15 V, V ₊ = -15 V, G = 100			90		
		V ₋ = -5 V to -15 V, V ₊ = +15 V, G = 10			70		
		V ₋ = -5 V to -15 V, V ₊ = +15 V, G = 1			50		

See footnote at end of table.

**STANDARD
MICROCIRCUIT DRAWING**
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

REVISION LEVEL
D

5962-88630

SHEET
5

TABLE I. Electrical performance characteristics – Continued.

Test	Symbol	Conditions 1/ -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Common mode rejection	CMR	V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1000	1	01, 03	125		dB
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 100			120		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 10			100		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1			85		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1000	2, 3		120		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G= 100			115		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 10			95		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1			80		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1000	1	02	115		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 100			110		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 10			95		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1			75		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1000	2, 3		110		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G= 100			105		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 10			90		
		V _{CM} = ±10 V, 1 kΩ source imbalance, G = 1			75		

See footnote at end of table.

**STANDARD
MICROCIRCUIT DRAWING**
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

REVISION LEVEL
D

5962-88630
SHEET
6

TABLE I. Electrical performance characteristics – Continued.

Test	Symbol	Conditions ^{1/} -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Gain equation accuracy	GE	G = 20R _S / R _G , T _A = +25°C Accuracy measured at G = 1, 10, 100, and 1000	1	01		0.6	%
				02, 03		0.8	
Gain range	G	T _A = +25°C	1	All	1	1000	V/V
Output short circuit current	I _{OS+}	T _A = +25°C	1	All	60	120	mA
	I _{OS-}				-120	-60	
Reference input resistance	R _{INREF}	T _A = +25°C	1	All	35	65	kΩ
Quiescent current	I _Q	+V linked to +V _{OP} -V linked to -V _{OP}	1, 2, 3	All		4.8	mA
Input offset voltage	V _{IOS}		4	01		50	μV
			5, 6			80	
			4	02, 03		100	
			5, 6			150	
Output offset voltage	V _{OOS}		4	01		3	mV
			5, 6			6	
			4	02, 03		6	
			5, 6			10	
Output offset voltage drift	TCV _{OOS}	R _G = ∞	8	01, 03		50	μV/°C
				02		120	

See footnote at end of table.

**STANDARD
MICROCIRCUIT DRAWING**
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

REVISION LEVEL
D

5962-88630

SHEET
7

TABLE I. Electrical performance characteristics – Continued.

Test	Symbol	Conditions ^{1/} -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Output voltage swing	V _O	R _L = 500 Ω, 2 kΩ	4	All	±13		V
		R _L = 50 Ω			±2.5		
		R _L = 500 Ω, 2 kΩ	5, 6		±12		
Slew rate	SR	G = 10	4	01	3.5		V/μs
			5, 6		2.75		
			4	02, 03	3.0		
			5, 6		2.0		
Average input offset voltage drift	TCV _{IOS}	T _A = -55°C, +125°C	8	01	0.3		μV/°C
				02, 03	1.0		

^{1/} V_S = ±15 V, R_S = 10 kΩ, R_L = 2 kΩ, unless otherwise specified.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 or for device class M in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DSCC-VA of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change as defined in MIL-PRF-38535, appendix A.

3.9 Verification and review for device class M. For device class M, DSCC, DSCC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device class M. Device class M devices covered by this drawing shall be in microcircuit group number 49 (see MIL-PRF-38535, appendix A).

**STANDARD
MICROCIRCUIT DRAWING**
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88630

REVISION LEVEL
D

SHEET
8

Device types	01 and 02		03
Case outlines	V	3	K
Terminal number	Terminal symbol		
1	R _G	NC	R _{G2}
2	R _G	R _G	R _{G1}
3	-IN	R _G	-IN
4	V _{OOS} NULL	-IN	NC
5	V _{OOS} NULL	NC	V _{OOS} NULL
6	TEST PIN	V _{OOS} NULL	NC
7	SENSE	NC	V _{OOS} NULL
8	REFERENCE	V _{OOS} NULL	TEST PIN
9	OUTPUT	NC	NC
10	-V _{OP}	TEST PIN	NC
11	V-	NC	SENSE
12	V+	SENSE	REFERENCE
13	+V _{OP}	REFERENCE	OUTPUT
14	R _S	OUT	-V _{OP}
15	R _S	NC	NC
16	V _{IOS} NULL	-V _{OP}	V-
17	V _{IOS} NULL	NC	V+
18	+IN	V-	+V _{OP}
19	---	V+	NC
20	---	NC	R _{S2}
21	---	+V _{OP}	R _{S1}
22	---	R _S	V _{IOS} NULL
23	---	R _S	V _{IOS} NULL
24	---	NC	+IN
25	---	V _{IOS} NULL	---
26	---	V _{IOS} NULL	---
27	---	NC	---
28	---	+IN	---

FIGURE 1. Terminal connections.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88630
		REVISION LEVEL D	SHEET 9

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. For device class M, sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection.

4.2.1 Additional criteria for device class M.

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015.

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table IIA herein.

4.2.2 Additional criteria for device classes Q and V.

a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.

b. Interim and final electrical test parameters shall be as specified in table IIA herein.

c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections and as specified herein. Quality conformance inspection for device class M shall be in accordance with MIL-PRF-38535, appendix A and as specified herein. Inspections to be performed for device class M shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4.1 Group A inspection.

a. Tests shall be as specified in table IIA herein.

b. Subgroups 7, 9, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88630
		REVISION LEVEL D	SHEET 10

TABLE IIA. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class M	Device class Q	Device class V
Interim electrical parameters (see 4.2)	1	1	1
Final electrical parameters (see 4.2)	1, 2, 3, 4, 5, 6, 8 <u>1/</u>	1,2,3,4,5,6,8 <u>1/</u>	1,2,3,4,5,6,8 <u>1/ 2/</u>
Group A test requirements (see 4.4)	1, 2, 3, 4, 5, 6, 8	1,2,3,4,5,6,8	1,2,3,4,5,6,8
Group C end-point electrical parameters (see 4.4)	1	1	1 <u>2/</u>
Group D end-point electrical parameters (see 4.4)	1	1	1
Group E end-point electrical parameters (see 4.4)	---	---	---

1/ PDA applies to subgroup 1.

2/ Delta limits in accordance with table IIB shall be computed with reference to the previous interim electrical parameters.

Table IIB. 240 hour burn-in and group C end-point electrical parameters.

Parameter	Device type	Limit		Delta	
		Min	Max	Min	Max
V _{IOS}	01		50 μ V		40 μ V
	03		100 μ V		40 μ V
V _{OOS}	01		3 mV		6 mV
	03		6 mV		6 mV
I _{B+}	01, 03		4 nA		3 nA
I _{B-}	01, 03		4 nA		3 nA

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.2.1 Additional criteria for device class M. Steady-state life test conditions, method 1005 of MIL-STD-883:

- Test condition A, B, C or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.
- T_A = +125°C, minimum.
- Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88630
		REVISION LEVEL D	SHEET 11

4.4.2.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

- a. End-point electrical parameters shall be as specified in table IIA herein.
- b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. For device class M, the devices shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535, appendix A for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = +25^{\circ}\text{C} \pm 5^{\circ}\text{C}$, after exposure, to the subgroups specified in table IIA herein.
- c. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform Defense Supply Center Columbus when a system application requires configuration control and which SMD's are applicable to that system. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0544.

6.4 Comments. Comments on this drawing should be directed to DSCC-VA, Columbus, Ohio 43216-5000, or telephone (614) 692-0547.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DSCC-VA and have agreed to this drawing.

6.6.2 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DSCC-VA.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88630
		REVISION LEVEL D	SHEET 12

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 02-11-22

Approved sources of supply for SMD 5962-88630 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535.

Standard microcircuit drawing PIN <u>1/</u>	Vendor CAGE number	Vendor similar PIN <u>2/</u>
5962-8863001VA	24355	AMP-01AX/883
5962-8863001VKA	24355	AMP01AN/QMLV
5962-8863001VVA	24355	AMP01AD/QMLV
5962-8863002VA	24355	AMP-01BX/883
5962-88630023A	24355	AMP-01BTC/883
5962-8863003VVA	24355	AMP01D/QMLV
5962-8863003VKA	24355	AMP01N/QMLV

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

24355

Vendor name
and address

Analog Devices
Route 1 Industrial Park
P.O. Box 9106
Norwood, MA 02062
Point of contact: 1500 Space Park Drive
P.O. Box 58020
Santa Clara, CA 95052-8020

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.